











Leuchtmittel - Metalldampf lampen - Energiesparlampen

Art.-Nr.	Typ	Socket
A		
Cardanlight Metalldampf lampen G12		
Approbation: CE		
		
CATG1270W3000	Metalldampf lampen 70 W, 3000K	G12
CATG1270W4000	Metalldampf lampen 70 W, 4000K	G12
CATG12150W3000	Metalldampf lampen 150 W, 3000K	G12
CATG12150W4000	Metalldampf lampen 150 W, 4000K	G12
CATG12250W6000	Metalldampf lampen 250 W, 6000K	G12
B		
Cardanlight Metalldampf lampen R7s/FC2		
Approbation: CE		
		
CAT70W3000	Metalldampf lampen 70 W, 3000K	R7s
CAT70W6000	Metalldampf lampen 70 W, 6000K	R7s
CAT70W10000	Metalldampf lampen 70 W, 10000K	R7s
CAT70W14000	Metalldampf lampen 70 W, 14000K	R7s
CAT150W3000	Metalldampf lampen 150 W, 3000K	R7s
CAT150W6000	Metalldampf lampen 150 W, 6000K	R7s
CAT150W10000	Metalldampf lampen 150 W, 10000K	R7s
CAT150W14000	Metalldampf lampen 150 W, 14000K	R7s
CAT250W4000	Metalldampf lampen 250 W, 4000K	FC2
CAT250W6000	Metalldampf lampen 250 W, 6000K	FC2
CAT250W10000	Metalldampf lampen 250 W, 10000K	FC2
C		
Mini Spiral Energiespar lampen E27		
Approbation: CE		
		
METH5431756	Mini Spiral Energiespar 11 W, 230 V 2700 K / 550 lumen	E27
METH5431773	Mini Spiral Energiespar 15 W, 230 V 2700 K / 750 lumen	E27
METH5431822	Mini Spiral Energiespar 20 W, 230 V 2700 K / 1000 lumen	E27
D		
Philips Ecotone Twister Energiespar lampen 80W, E40		
Approbation: CE		
		
PHCH768282	Philips Ecotone Twister 80 W, 230 V 6500 K / 5300 lumen	E40

Art.-Nr.	Typ	Lichtfarbe	Socket
A			
LED 1W / 3W / 5W			
Approbation: CE			
XI0001	1W LED Lampe 12 V	weiß	GX5,3
XI0003	3W LED Lampe 12 V	weiß	GX5,3
XI0002	1W LED Lampe 230 V	weiß	GU10
XI0004	3W LED Lampe 230 V	weiß	GU10
XI0005	3W LED Lampe 230 V	warmweiß	GU10
XI0006	5W LED Lampe 230 V	weiß	GU10
XI0007	5W LED Lampe 230 V	warmweiß	GU10
			
B			
LED 3 x 1W			
Approbation: CE			
SI153239	3 x 1W LED Lampe 230 V	3200 K	GU10
			
C			
LED CHIP G9 230 V			
inkl. 48 x SMD LEDs 190 lm, Abstrahlwinkel je LED 120°, ø 31 mm, Höhe 65 mm			
Approbation: CE			
CHI19649	LED CHIP 230 V	3000K	G9
			
D			
LED QR111 11W			
inkl. Kühler, Material: Aluminium			
Sicherheitsabstand: 0,1 m			
Schutzart: IP20			
Approbation: CE			
BRIAR111VF101S	11W LED, 12 V Lampe mit Reflektor 45°	3000 K	G53
	